

Data Sheet

Constellation® ES

High-Capacity Storage Designed for
Seamless Enterprise Integration

Key Advantages

- Fifth-generation, enterprise, nearline drive designed for 24x7 operation
- Up to 2TB capacity for data-hungry enterprise business applications
- Best-in-class rotational vibration tolerance ensures unrivalled performance in high-density applications for continuous data access.
- Enhanced efficiencies with PowerChoice™ host-selectable power options for unprecedented savings during slow or idle periods
- Seagate RAID Rebuild™ development platform significantly reduces hours of lost productivity.
- Multi-drive firmware maximized for enterprise system availability
- 6Gb/s SAS performance with error detection and correction (IOEDC/IOECC) capabilities and PI (Protection Information)
- Self-Encrypting Drive (SED) option cuts IT drive retirement expenses while securely protecting data and is one of the easiest, most cost-effective security measures you can implement.¹
- FIPS Self-Encrypting Drive option provides all the benefits of SED and is NIST certified to meet U.S., Canada and U.K. government data encryption compliance requirements.^{1,2}

Best-Fit Applications

- High-capacity data center storage
- Mainstream enterprise external storage arrays
- Enterprise backup and restore
- Cloud storage

¹ Self-Encrypting Drive (SED) and FIPS Self-Encrypting Drive options may require TCG-compliant host or controller support. Not available in all countries.

² See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1636>



Constellation® ES

High-Capacity Storage Designed for Seamless Enterprise Integration



Specifications	6Gb/s SAS			SATA 6Gb/s		
	2TB ¹	1TB ¹	500GB ¹	2TB ¹	1TB ¹	500GB ¹
Standard Model	ST2000NM0001 ⁶	ST1000NM0001 ⁶	ST500NM0001 ⁶	ST2000NM0011	ST1000NM0011	ST500NM0011
SED 256 Model	ST2000NM0021 ²	ST1000NM0021 ²	ST500NM0021 ²	ST2000NM0031 ²	ST1000NM0031 ²	ST500NM0031 ²
SED 128 with FIPS Model	ST2000NM0041 ³	ST1000NM0041 ³	ST500NM0041 ³	ST2000NM0051 ³	ST1000NM0051 ³	ST500NM0051 ³
Features						
Protection Information	Yes ⁶	Yes ⁶	Yes ⁶	—	—	—
Low Halogen	Yes	Yes	Yes	Yes	Yes	Yes
Self-Encrypted Drive (SED) Option	Yes	Yes	Yes	Yes	Yes	Yes
Configuration/Organization						
Bytes per Sector	512, 520, 528	512, 520, 528	512, 520, 528	512	512	512
Reliability/Data Integrity						
Power-On Hours (annual)	8760	8760	8760	8760	8760	8760
Mean Time Between Failures (MTBF, hours)	1.2 million	1.2 million	1.2 million	1.2 million	1.2 million	1.2 million
Reliability Rating at Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%	0.73%	0.73%
Nonrecoverable Read Errors per Bits Read	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15
IOEDC (I/O Error Detection Code)	Reads/Writes	Reads/Writes	Reads/Writes	Reads/Writes	Reads/Writes	Reads/Writes
IOECC (I/O Error Correction Code)	Reads/Writes	Reads/Writes	Reads/Writes	Writes	Writes	Writes
Load/Unload Cycles (at 40°C)	300,000	300,000	300,000	300,000	300,000	300,000
Interface Ports	Dual	Dual	Dual	Single	Single	Single
Limited Warranty (years) ⁴	3	3	3	3	3	3
Performance						
Spindle Speed (RPM)	7200	7200	7200	7200	7200	7200
Seek Time, Average Read/Write (ms)	8.5/9.5	8.5/9.5	8.5/9.5	8.5/9.5	8.5/9.5	8.5/9.5
Max Sustained Transfer Rate (MB/s)	150	150	150	140	140	140
Cache, Multisegmented (MB)	64	64	64	64	64	64
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5
Rotational Vibration @ 1500Hz (rad/s ²)	12.5	12.5	12.5	12.5	12.5	12.5
Power Management						
Power Supply Requirements	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V	+12V and +5V
Idle (W)	7.26	5.41	4.67	6.39	4.61	3.74
Typical Operating Power (W)						
Random Read	10.43	8.04	7.89	9.03	7.42	6.47
Random Write	10.15	7.28	7.18	7.80	6.21	5.31
PowerChoice™ Option (W)	As low as 1.39	As low as 1.34	As low as 1.44	As low as 0.53	As low as 0.57	As low as 0.55
Environmental						
Operating Temperature Range (°C)	5 to 60	5 to 60	5 to 60	5 to 60	5 to 60	5 to 60
Vibration (Gs)						
Operating: 5 to 500Hz	0.5	0.5	0.5	0.25	0.25	0.25
Nonoperating: 10 to 500Hz	2.0	2.0	2.0	4.9	4.9	4.9
Shock (Gs)						
Operating, 2ms	70	70	70	70	70	70
Nonoperating: 1ms and 2ms	300	350	350	300	350	350
Physical						
Height (in/mm) ⁵	1.028/26.10	1.028/26.10	1.028/26.10	1.028/26.10	1.028/26.10	1.028/26.10
Width (in/mm) ⁵	4.010/101.85	4.010/101.85	4.010/101.85	4.010/101.85	4.010/101.85	4.010/101.85
Depth (in/mm) ⁵	5.787/147.00	5.787/147.00	5.787/147.00	5.787/147.00	5.787/147.00	5.787/147.00
Weight (lb/g)	1.577/710	1.41/640	1.34/610	1.577/710	1.411/640	1.345/610
Carton Unit Quantity	20	20	20	20	20	20
Cartons per Pallet	40	40	40	40	40	40
Cartons per Layer	8	8	8	8	8	8

1 One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

2 Self-Encrypting Drive model. May require TCG-compliant host or controller support. Not available in all countries.

3 FIPS Self-Encrypting Drive model. May require TCG-compliant host or controller support. Not available in all countries.

4 Nearline products shipped on or after December 31, 2011, have a 3-year limited warranty. Nearline products shipped before December 31, 2011, have a 5-year limited warranty.

5 These base deck dimensions conform to the Small Form Factor Standard (SFF-8301) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8323.

6 Protection Information included

www.seagate.com



FIPS 140-2 INSIDE

AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

Copyright © 2011 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Constellation and PowerChoice are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The FIPS logo is a certification mark of NIST, which does not imply product endorsement by NIST, the U.S., or Canadian governments. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. The export or re-export of hardware or software containing encryption may be regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and controlled for import and use outside of the U.S. Seagate reserves the right to change, without notice, product offerings or specifications. DS1697.6-1112US, December 2011