

Enterprise Capacity 3.5 HDD (Helium)

Channel Data Sheet

Maximum Storage Capacity for Highest Rack Space Efficiency

- 10TB per drive¹ for 25% more petabytes per rack²
- Industry's lowest power and weight for optimum data center TCO
- Highest 10TB HDD performance with enhanced caching, making it perfect for OLTP and HPC application
- Hyperscale SATA model tuned for large data transfers
- PowerBalance™ feature optimizes IOPS/Watt
- Advanced Write Caching feature for 20% boost in random write performance²
- Forged, wrought-aluminum base and a helium sealed-drive design with no porosity and uniform density
- Superior material and weld-width design for a more robust, hermetically sealed-drive enclosure that protects from helium leaks
- Digital environmental sensors for measuring internal humidity, pressure and temperature, helping to ensure high reliability, performance and quality
- Latest hermetic interconnect technology supporting higher data rate heads and higher pin counts for extreme thermal conditions
- Proven enterprise-class reliability backed by 2.5M-hr MTBF



Best-Fit Applications

- Hyperscale applications/cloud data centers
- Massive scale-out data centers
- OLTP and HPC applications
- High-capacity density RAID storage
- Mainstream enterprise external storage arrays
- Distributed file systems, including Hadoop and Ceph
- Enterprise backup and restore—D2D, virtual tape
- Centralized surveillance

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

² Compared to 8TB competitive product.

Enterprise Capacity 3.5 HDD (Helium)



Specifications	SATA 6Gb/s Hyperscale		SATA 6Gb/s Standard		12Gb/s SAS Standard
	10TB	8TB	10TB	8TB	10TB
Capacity	10TB	8TB	10TB	8TB	10TB
Standard Model (512e) ¹	—	—	ST10000NM0086	ST8000NM0206	ST10000NM0096
Hyperscale Model (512e) ¹	ST10000NM0016	ST8000NM0016	—	—	—
Standard Model (4Kn) ¹	—	—	ST10000NM0146	—	ST10000NM0206
SED Model (512e) ^{1,2}	—	—	ST10000NM0156	—	ST10000NM0216
SED Model (4Kn) ^{1,2}	—	—	ST10000NM0166	—	ST10000NM0226
SED-FIPS Model (512e) ^{1,2,3}	—	—	ST10000NM0176	—	ST10000NM0236
SED-FIPS Model (4Kn) ^{1,2,3}	—	—	ST10000NM0186	—	ST10000NM0246
Features					
Helium Sealed-Drive Design With Wide Weld	Yes	Yes	Yes	Yes	Yes
Digital Environmental Sensors	Yes	Yes	Yes	Yes	Yes
Protection Information (T10 DIF)	—	—	—	—	Yes
SuperParity	Yes	Yes	Yes	Yes	Yes
PowerChoice™/PowerBalance™ Technology	Yes	Yes	Yes	Yes	Yes
Low Halogen/Hot-Plug Support ⁴	Yes	Yes	Yes	Yes	Yes
Cache, Multisegmented (MB)	256	256	256	256	256
Organic Solderability Preservative	Yes	Yes	Yes	Yes	Yes
Reliability/Data Integrity					
Mean Time Between Failures (MTBF, hours)	2.5 Million	2.5 Million	2.5 Million	2.5 Million	2.5 Million
Reliability Rating @ Full 24x7 Operation (AFR)	0.35%	0.35%	0.35%	0.35%	0.35%
Nonrecoverable Read Errors per Bits Read	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15
Power-On Hours per Year (24x7)	8760	8760	8760	8760	8760
512e Sector Size (Bytes per Sector)	512	512	512	512	512, 520, 528
4Kn Sector Size (Bytes per Sector)	—	—	4096	4096	4096, 4160, 4224
Limited Warranty (years)	5	5	5	5	5
Performance					
Spindle Speed (RPM)	7200	7200	7200	7200	7200
Interface Access Speed (Gb/s)	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	6.0, 3.0, 1.5	12.0, 6.0, 3.0
Max. Sustained Transfer Rate OD (MB/s, MiB/s)	249MB/s	249MB/s	254MB/s	249MB/s	254MB/s
Random Read/Write 4K QD16 WCD (IOPS)	170, 138	170, 138	170, 370	170, 370	170, 370
Average Latency (ms)	4.16	4.16	4.16	4.16	4.16
Interface Ports	Single	Single	Single	Single	Dual
Rotational Vibration @ 1500Hz (rad/s ²)	12.5	12.5	12.5	12.5	12.5
Power Consumption					
Idle A (W) Average	4.5W	4.5W	4.5W	4.5W	5.5W
Max Operating Power, Random Write (WCD) 4K/4Q RR50% / RW50%	8.0	8.0	8.0	8.0	9.0
Max Operating Power, Random Read 4K/16Q (W)	8.4	8.4	8.4	8.4	9.4
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V	+12 V and +5 V
Environmental					
Temperature, Operating (°C)	5°C – 60°C	5°C – 60°C	5°C – 60°C	5°C – 60°C	5°C – 60°C
Vibration, Nonoperating: 10Hz to 500Hz (Gms)	2.27	2.27	2.27	2.27	2.27
Shock, Operating 2ms (Read/Write) (Gs)	70/40Gs	70/40Gs	70/40Gs	70/40Gs	70/40Gs
Shock, Nonoperating, 1ms/2ms (Gs)	250Gs	250Gs	250Gs	250Gs	250Gs
Physical					
Height (mm/in, max) ⁵	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max) ⁵	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in
Depth (mm/in, max) ⁵	147.0mm/5.787in	147.0mm/5.787in	147.0mm/5.787in	147.0mm/5.787in	147.0mm/5.787in
Weight (g/lb)	650g/1.433lb	650g/1.433lb	650g/1.433lb	650g/1.433lb	650g/1.433lb
Carton Unit Quantity	20	20	20	20	20
Cartons per Pallet / Cartons per Layer	40 / 8	40 / 8	40 / 8	40 / 8	40 / 8

¹ Invoice SPA required for all 8TB models and most SED and SED-FIPS models

² Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support.

³ See FIPS 140-2 Level 2 Certificate at: <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>

⁴ Supports Hotplug operation per Serial ATA Revision 2.6 specification.

⁵ These base deck dimensions conform to the Small Form Factor Standard (SFF-8301) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8323.

SEAGATE.COM

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000

ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888

EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00